

LED PANEL

LED LIGHT



DOB FULL PLASTIC SLIM PANEL
RECESSED TYPE


A⁺



Specification

| | | | | |
|----------------|------------------|-------------------|-------------------|-------------------|
| 5W | 9W | 12W | 18W | 24W |
| 3CCT | 3CCT | 3CCT | 3CCT | 3CCT |
| 120° | 120° | 120° | 120° | 120° |
| 25000h | 25000h | 25000h | 25000h | 25000h |
| PF>0.5 | PF>0.5 | PF>0.5 | PF>0.5 | PF>0.5 |
| IP>20 | IP>20 | IP>20 | IP>20 | IP>20 |
| AC165-265V | AC165-265V | AC165-265V | AC165-265V | AC165-265V |
| 50/60 Hz | 50/60 Hz | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| φ95*25/70-80mm | φ119*26/95-110mm | φ149*27/120-140mm | φ176*28/145-165mm | φ220*30/185-210mm |

*Remarks: For more sizes available, contact MILANLUX salesman for full information.



2
A R O S
GARANTIA

NO
UV/IR

NOT
DIMMABLE

INSTANT LIGHT
0.3sed

25.000h

50.000
ON OFF

CE

RoHS
2002/95/EC

RECYCLED

NO
MERCURY

Hg
0,0mg

CO₂